





Comfort EVO

Comfort EVO Tunable White OCTO Smart Control
Code: ACOM/1/TW/OCTO

| | |
|---------------|---|
| Category | Downlights |
| Application | Ancillary, Commercial, Education, Healthcare, Hospitality, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Deep cut-off angle for glare control and comfort
- Full dimming control and circadian rhythm option via Casambi App
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities
- Intelligent and eco-friendly 3 part design allows end user the choice of either black or white reflector and trim accessories to add to the downlight (ACOM*/1), offering great customisation and product upgradability
- One product provides complete control of colour temperature selection, ranging between 2700K and 6500K. Colour selection achieved via the Casambi App
- Downlight design allows installation into existing hole cut-outs of 210mm
- Polycarbonate housing with unique thermal management for durability and optimum lifespan

GENERAL INFORMATION

| | |
|----------------------------------|-----------------------------------|
| Wattage | 35W |
| Lumens Delivered | 3500lm - 3700lm (2700K - 6500K) |
| Lm/W | 100lm/W - 104lm/W (2700K - 6500K) |
| Beam Angle | 80 |
| CRI | 80 |
| CCT | 2700-6500K |
| Input | 220/240V |
| Operating Temp | -15°C - 40°C |
| SDCM | 3 |
| UGR | 24 |
| Cut-Out Size | 210mm |
| Product Weight without Packaging | 0.37 kg |

TECHNICAL INFORMATION

| | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 60,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 62 mm |

