





# Comfort EVO

Comfort EVO Tunable White OCTO Smart Control

Code: ACOM/1/TW/OCTO



Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Deep cut-off angle for glare control and comfort
- Full dimming control and circadian rhythm option via Casambi App
- Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities

- Intelligent and eco-friendly 3 part design allows end user the choice of either black or white reflector and trim accessories to add to the downlight (ACOM\*1), offering great customisation and product upgradability
- One product provides complete control of colour temperature selection, ranging between 2700K and 6500K. Colour selection achieved via the Casambi App
- Downlight design allows installation into existing hole cut-outs of 210mm
- Polycarbonate housing with unique thermal management for durability and optimum lifespan

GENERAL INFORMATION	
Voltage	35W
Lumens Delivered	3500lm - 3700lm (2700K - 6500K)
Lm/W	100lm/W - 104lm/W (2700K - 6500K)
Beam Angle	80
CRI	80
CCT	2700-6500K
Input	220-240V
Operating Temp	-15°C - 40°C
SDCM	3
UGR	24
Cut-Out Size	210mm
Product Weight without Packaging	0.37 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 60,000h
Warranty (Years)	5
CE Mark	Yes
Height	62 mm