



Comfort EVO

Part of the Downlights product category



Model	Comfort EVO 2 Dual Output CCT Downlight Switch Dim
Code	ACOM2/1/DD1
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	21W
Operating Temp	-20°C - 25°C
Lumens Delivered	2300lm - 2800lm (4000K)
lm/W	130lm/W (4000K)
CCT	3000/4000K
UGR	23
Beam Angle	80

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.23 kg
Colour / Finish	White
Height	62 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.85
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES


- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Intelligent and eco-friendly 3 part design allows end user the choice of either black or white reflector and trim accessories to add to the downlight (ACOM*/1), offering great customisation and product upgradability
- Deep cut-off angle for glare control and comfort
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Downlight design allows installation into existing hole cut-outs of 210mm

ACCESSORIES

ACOM/TR/W/1	Comfort EVO White Reflector and Trim
ACOM/TR/S/1	Comfort EVO Satin Chrome Reflector and White Trim
ACOM/TR/P/1	Comfort EVO Polished Chrome Reflector and White Trim
ACOM/TR/B/1	Comfort EVO Black Reflector and Trim
AARXDLK/1	ARX Downlight Anti-Ligature Kit
AHUEMKIT/LI	Hawk Universal Lithium Emergency Kit Maintained/Non-maintained

ACCESSORIES

ACOM/TR/W/1	Comfort EVO White Reflector and Trim
ACOM/TR/B/1	Comfort EVO Black Reflector and Trim





Comfort EVO

Part of the Downlights product category



Model	Comfort EVO 2 Dual Output CCT Downlight Switch Dim
Code	ACOM2/1/DD1
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

