









Commercial Linear

Performance

Ancillary, Commercial, Education




Crescent

Crescent CCT Surface/Suspended Linear Code: ACRESLED4/DD1/M3








Category

Application

Specification



- High specification fully enclosed linear luminaire suitable for most commercial and educational applications
- Polycarbonate diffuser and polished louvre for excellent photometric performance
- Suitable for surface mounting and suspension

www.ansell-lighting.com

- Steel powder coated body for enhanced durability
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- · Powered by Philips

GENERAL INFORMATION		
Wattage	35W	
Lumens Delivered	3100lm - 4900lm (4000K)	
Lm/W	146-139lm/W (4000K)	
Beam Angle	80	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	0°C - 50°C	
SDCM	3	
UGR	18	
Product Weight without Packaging	3.06 kg	

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Suspended
Lumen Depreciation	L80 100,000h
Warranty (Years)	5
CE Mark	Yes

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750