









Commercial Linear

Performance

Ancillary, Commercial, Education




Crescent

Crescent CCT Surface/Suspended Linear Code: ACRESLED4








Category

Application

Specification



- High specification fully enclosed linear luminaire suitable for most commercial and educational applications
- Polycarbonate diffuser and polished louvre for excellent photometric performance
- Suitable for surface mounting and suspension

www.ansell-lighting.com

- Steel powder coated body for enhanced durability
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- · Powered by Philips

GENERAL INFORMATION		
Wattage	21W - 35W	
Lumens Delivered	3100lm - 4900lm (4000K)	
Lm/W	146-139lm/W (4000K)	
Beam Angle	80	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	-20°C - 50°C	
SDCM	3	
UGR	18	
Product Weight without Packaging	2.96 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 100,000h	
Warranty (Years)	5	
CE Mark	Yes	
Accessories	ASK1	