



Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

## Camini

CAMINI LED 3W GRAPHITE Code: ACSQLEDWL

## PRODUCT FEATURES

- Compact low level square LED pathway light with downward light spill suitable for residential and hospitality applications
- CCT selectable between 3000K and 4000K
- Non-dimmable

- Die-cast aluminium construction with graphite paint finish
- Supplied c/w plastic installation box and pre-wired with 1 metre of rubber insulated cable for ease of installation

GENER	AL INFORMATION	
Wattage	2	
Lumens Delivered	80lm	
Lm/W	22Im/W	
Beam Angle	70	
CRI	80	
ССТ	3000K/4000K	
Input	220-240V	
Operating Temp	-20°C - 25°C	
SDCM	3	
Cut-Out Size	82.5x82.5mm	
Energy efficiency class	E	
Product Weight without Packaging	0.589 kg	

TECHNICAL	. Information
Light Source	LED
Colour / Finish	Graphite
IP Rating	IP65
IK Rating	IKO2
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	3
CE Mark	Yes
Height	96 mm











Category	Wall Lights
Application	Hospitality, Outdoor, Residential, Retail
Specification	Architectural

## Camini

## **CAMINI LED 3W GRAPHITE** Code: ACSQLEDWL







