



Condor



Part of the Emergency product category

Model	Condor Twin Spot Non-Maintained Black
Code	ACTSLED/B/3NM
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	3W
Operating Temp	0°C - 40°C
Lumens Delivered	440lm (Emergency)
lm/W	146lm/W
CCT	6500K
Beam Angle	70

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.8 kg
Colour / Finish	Black
Height	221 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	65
Internal / External	Internal
Surface / Recessed / Suspended	Wall
Power Factor	0.42
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Sleek modern polycarbonate moulded decorative twin spot
- Individual adjustable LED arrays allowing the end user to aim output into the desired location
- Decorative design suitable for retail application
- Available in black and white finishes
- Self-test as standard





Condor



Part of the Emergency product category

- Model** Condor Twin Spot Non-Maintained Black
- Code** ACTSLED/B/3NM
- Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

