



Cubba



Part of the Wall Lights product category

Model	Cubba CCT Multi Wattage Black
Code	ACUB/1/BK
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	13W - 23W
Operating Temp	-20°C to 40°C
Lumens Delivered	1750lm - 3200lm (4000K)
lm/W	135lm/W - 140lm/W (4000K)
CCT	3000/4000K
UGR	25
Beam Angle	107

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	2.1 kg
Colour / Finish	Black

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Surface, Wall
Power Factor	0.9
L70 @ 25°C	L70 72,000h

PRODUCT FEATURES

- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for education, commercial and industrial applications
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Integrated switch on the LED board allows for the section behind the eyelid to be deactivated, improving energy efficiency when using the eyelid trim
- Gear tray located on the diffuser, allowing the base to be installed and then the diffuser connected, this coupled with removeable conduit entries on base ensure a quick and simple installation
- Side conduit entry points for ease of installation

ACCESSORIES

AXPC/1/3NM	XPRESS Compact Emergency Kit
AXPC/1/3NM/DA	XPRESS Compact DALI Emergency Kit
AXPC/CF/1	XPRESS Compact Clip-In Microwave sensor with Corridor Function
AXPC/PC/1	XPRESS Compact Clip-In Photocell





Cubba



Part of the Wall Lights product category

Model	Cubba CCT Multi Wattage Black
Code	ACUB/1/BK
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

