



Defender



Part of the Commercial Panels product category

Model	Defender CCT Multi Wattage IP65 Panel Emergency
Code	ADELED/M3
Application	Ancillary, Commercial, Education, Healthcare, Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	20W - 33W
Operating Temp	0°C - 50°C
Lumens Delivered	2800lm - 4500lm (4000K)
lm/W	141lm/w - 135lm/W (4000K)
CCT	4000/6500K
UGR	17
Beam Angle	110

MATERIAL INFORMATION

Product Weight without	8.31 kg
Packaging	
Colour / Finish	White
Height	115 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Backlit clean air LED panel suitable for education, commercial and healthcare applications
- High quality steel housing with welded frame and secured by Easy Fix style brackets
- Selectable CCT between 4000K and 6500K output
- Frame fitted with TP(a) rated diffuser providing excellent diffusion and outstanding light transmission
- Powered by Tridonic





Defender



Part of the Commercial Panels product category

Model	Defender CCT Multi Wattage IP65 Panel Emergency
Code	ADELED/M3
Application	Ancillary, Commercial, Education, Healthcare, Industrial

