# Degree

5YR IP20 IK06

Part of the Bulkheads product category

| | |
|---|---|
| **Model** | Degree XPRESS Surface Mounted Cornice 1200mm |
| **Code** | ADGRE4/2 |
| **Application** | Commercial, Education, Healthcare |

## GENERAL INFORMATION

| | |
|---|---|
| **Input** | 220-240V |
| **Wattage** | 15W - 25W |
| **Operating Temp** | -20°C - 40°C |
| **Lumens Delivered** | 1800lm - 2900lm (4000K) |
| **lm/W** | 116lm/W |
| **CCT** | 3000/4000/5000K |
| **UGR** | 33 |
| **Beam Angle** | 80/120 |

## MATERIAL INFORMATION

| | |
|---|---|
| **Main Material** | Steel |
| **Diffuser Material** | Polycarbonate |
| **Product Weight without Packaging** | 3.13 kg |
| **Colour / Finish** | White |
| **Height** | 104 mm |

## TECHNICAL INFORMATION

| | |
|---|---|
| **Class Protection** | 1 |
| **Light Source** | LED |
| **SDCM (Initial Macadam)** | 3 |
| **CRI** | 80 |
| **Internal / External** | Internal |
| **Surface / Recessed / Suspended** | Surface |
| **Power Factor** | 0.9 |
| **L70 @ 25°C** | L70 72,000h |

## PRODUCT FEATURES

- Modern surface-mounted cornice luminaire with asymmetric light distribution, suitable for corridors and stairwells in education, commercial, and healthcare environments
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 3 outputs, in one luminaire
- Clip-in gear tray design ensures quick and hassle-free installation and maintenance
- End caps with pull-out conduit tabs simplify conduit mounting for seamless integration into solid ceilings
- Compatible with XPRESS emergency and microwave sensors

## ACCESSORIES

| | |
|---|---|
| AXPL/1/3NM | XPRESS Linear Emergency Kit |
| AXPL/1/3NM/DA | XPRESS Linear DALI Emergency Kit |
| AXPL/MWS/1 | XPRESS Linear Clip-in Microwave Sensor On/Off |
| AZH/RP/1 | Sensor Remote Programmer |





# Degree

5YR IP20 IK06

Part of the Bulkheads product category

| | |
|---|---|
| **Model** | Degree XPRESS Surface Mounted Cornice 1200mm |
| **Code** | ADGRE4/2 |
| **Application** | Commercial, Education, Healthcare |















