



Degree



Part of the Bulkheads product category

Model	Degree XPRESS Surface Mounted Cornice 1200mm
Code	ADGRE4/2
Application	Commercial, Education, Healthcare

GENERAL INFORMATION

Input	220-240V
Wattage	15W - 25W
Operating Temp	-20°C - 40°C
Lumens Delivered	1800lm - 2900lm (4000K)
lm/W	116lm/W
CCT	3000/4000/5000K
UGR	33
Beam Angle	80/120

MATERIAL INFORMATION

Main Material	Steel
Diffuser Material	Polycarbonate
Product Weight without Packaging	3.13 kg
Colour / Finish	White
Height	104 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Power Factor	0.9
L70 @ 25°C	L70 72,000h

PRODUCT FEATURES

- Modern surface-mounted cornice luminaire with asymmetric light distribution, suitable for corridors and stairwells in education, commercial, and healthcare environments
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 3 outputs, in one luminaire
- Clip-in gear tray design ensures quick and hassle-free installation and maintenance
- End caps with pull-out conduit tabs simplify conduit mounting for seamless integration into solid ceilings
- Compatible with XPRESS emergency and microwave sensors

ACCESSORIES

AXPL/1/3NM	XPRESS Linear Emergency Kit
AXPL/1/3NM/DA	XPRESS Linear DALI Emergency Kit
AXPL/MWS/1	XPRESS Linear Clip-in Microwave Sensor On/Off
AZH/RP/1	Sensor Remote Programmer





Degree



Part of the Bulkheads product category

Model	Degree XPRESS Surface Mounted Cornice 1200mm
Code	ADGRE4/2
Application	Commercial, Education, Healthcare

