





@ansell_lighting









Disco EVO

Disco EVO 1 Emergency Code: ADIS1/1/M3

Reinforced Base

Reinforced base with a pre-drilled back entry and grommet for enhanced







Fast and Easy Install

Twist-on diffuser and 2-part design with push-fit terminals allow quick and easy installation









- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- · All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- · Instant light output and unlimited switching

- · High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- · Two options of microwave sensor emergency

GENERAL INFORMATION		
Wattage	5.5 - 9W	
Lumens Delivered	(4000K) 4W: 480lm 5W: 700lm 7W: 950lm	
Lm/W	(4000K) 4W: 120lm/W 5W: 140lm/W 7W:	
	140lm/W	
Beam Angle	110	
CRI	80	
CCT	3000/4000/6500K	
Input	220-240V	
Operating Temp	0°C - 40°C	
SDCM	3	
UGR	22	
Product Weight without Packaging	0.795 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	7	
CE Mark	Yes	
Diameter	275 mm	
Height	84 mm	