





@ansell\_lighting



**f** anselllighting



in Ansell Lighting



ansell\_lighting


## **Disco EVO**


## Disco EVO 1 Self-Test Emergency Code: ADIS1/1/SM3

Reinforced Base Reinforced base with a pre-drilled back entry and grommet for enhanced durability and effortiess installation



## Category Bulkheads **Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail Specification Performance





## PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- · All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- · Instant light output and unlimited switching

- High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- · Two options of microwave sensor emergency

	GENERAL INFORMATION
Wattage	5.5 - 9W
Lumens Delivered	(4000K) 4W: 480lm 5W: 700lm 7W: 950lm
Lm/W	(4000K) 4W: 120lm/W 5W: 140lm/W 7W:
	140lm/W
Beam Angle	110
CRI	80
CCT	3000/4000/6500K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
UGR	22
Product Weight without Packagin	ng 0.8 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	7	
CE Mark	Yes	
Diameter	275 mm	
Height	84 mm	

Belfast: +44 (0) 2890 773750