






Disco EVO

Disco EVO 2 Corridor Function Emergency Code: ADIS2/1/CF/M3

Category	Bulkheads
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail
Specification	Performance



PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- Instant light output and unlimited switching
- High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Two options of microwave sensor emergency

GENERAL INFORMATION

Wattage	10 - 18W
Lumens Delivered	(4000K) 9W: 1200lm 12W: 1800lm 16W: 2300lm
Lm/W	(4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W
Beam Angle	110
CRI	80
CCT	3000/4000/6500K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
UGR	26
Product Weight without Packaging	1.1 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L70 54,000h
Warranty (Years)	7
CE Mark	Yes
Diameter	325 mm
Height	85 mm

