





Disco EVO

Disco EVO 2 Corridor Function
Code: ADIS2/1/CF

| | |
|---------------|--|
| Category | Bulkheads |
| Application | Ancillary, Commercial, Education, Healthcare, Hospitality, Residential, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- Instant light output and unlimited switching
- High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Two options of microwave sensor emergency

GENERAL INFORMATION

| | |
|----------------------------------|---|
| Wattage | 9W - 16W |
| Lumens Delivered | (4000K) 9W: 1200lm 12W: 1800lm 16W: 2300lm |
| Lm/W | (4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 3000/4000/6500K |
| Input | 220-240V |
| Operating Temp | -20°C - 40°C |
| SDCM | 5 |
| UGR | 26 |
| Product Weight without Packaging | 1.1 kg |

TECHNICAL INFORMATION

| | |
|--------------------------------|---------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP65 |
| Class Protection | 2 |
| Internal / External | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Wall |
| Lumen Depreciation | L70 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 325 mm |
| Height | 85 mm |

