



Disco EVO

Disco EVO 2 Microwave Sensor Emergency Code: ADIS2/1/MWS/M3



Reinforced Base

Reinforced base with a pre-drilled back entry and grommet for enhanced durability and effortless installation



Fast and Easy Install

Twist-on diffuser and 2-part design with push-fit terminals allow quick and easy installation



- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- Instant light output and unlimited switching

- High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Two options of microwave sensor emergency

GENERAL INFORMATION	
Voltage	10.5 - 18.5W
Lumens Delivered	(4000K) 9W: 1200lm 12W: 1800lm 16W: 2300lm
Lm/W	(4000K) 9W: 135lm/W 12W: 145lm/W 16W: 145lm/W
Beam Angle	110
CRI	80
CCT	3000/4000/6500K
Input	220-240V
Operating Temp	0°C - 40°C
SDCM	3
UGR	26
Product Weight without Packaging	1.085 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L70 54,000h
Warranty (Years)	7
CE Mark	Yes
Diameter	325 mm
Height	85 mm

