





@ansell\_lighting










## **Disco EVO**


## Disco EVO 2 Self-Test Emergency Code: ADIS2/1/SM3

Reinforced Base Reinforced base with a pre-drilled back entry and grommet for enhanced durability and effortiess installation		









## PRODUCT FEATURES

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- · All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- · Instant light output and unlimited switching

- High efficiency up to 145lm/W
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- · Two options of microwave sensor emergency

GENERAL INFORMATION			
Wattage	10 - 18W		
Lumens Delivered	(4000K) 9W: 1200m 12W: 1800Im 16W:		
	2300lm		
Lm/W	(4000K) 9W: 135lm/W 12W: 145lm/W 16W:		
Wattage Lumens Delivered  Lm/W  Beam Angle  CRI  CCT  Input  Operating Temp  SDCM  UGR	145lm/W		
Beam Angle	110		
CRI	80		
CCT	3000/4000/6500K		
Input	220-240V		
Operating Temp	0°C - 40°C		
SDCM	3		
UGR	26		
Product Weight without Packaging	1.025 kg		

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP65		
Class Protection	2		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Wall		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	7		
CE Mark	Yes		
Diameter	325 mm		
Height	85 mm		

Belfast: +44 (0) 2890 773750