





@ansell_lighting





in Ansell Lighting





Eclipse

Eclipse MultiLED CCT Corridor Function DALI-Code: AECLED/CH/CCT/CF/DM3









- · LED wall/ceiling luminaire with adjustable power and light output option suitable for education and commercial applications and ancillary areas
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and
- Spun aluminium base with dished opal Visiluxe diffuser

- One product with integral driver dip-switch
- Corridor function options available for effective reduction in energy consumption
- · BESA box fixing versatile mounting options

GENERAL INFORMATION	
Wattage	25W
Lumens Delivered	1200lm - 2800lm (4000K)
Lm/W	108lm/W - 114lm/W (4000K)
Beam Angle	110
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	0°C - 25°C
SDCM	6
Product Weight without Packaging	0.01 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Chrome	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	435 mm	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750