



# Eclipse

Eclipse MultiLED CCT DALI-Emergency White  
Code: AECLD/W/CCT/DM3

|               |                                                                   |
|---------------|-------------------------------------------------------------------|
| Category      | Bulkheads                                                         |
| Application   | Ancillary, Commercial, Education, Healthcare, Hospitality, Retail |
| Specification | Performance                                                       |



## PRODUCT FEATURES

- LED wall/ceiling luminaire with adjustable power and light output option suitable for education and commercial applications and ancillary areas
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K
- Spun aluminium base with dished opal Visiluxe diffuser
- One product with integral driver dip-switch
- Corridor function options available for effective reduction in energy consumption
- BESA box fixing versatile mounting options

| GENERAL INFORMATION              |                           |
|----------------------------------|---------------------------|
| Wattage                          | 11W - 25W                 |
| Lumens Delivered                 | 1200lm - 2800lm (4000K)   |
| Lm/W                             | 108lm/W - 114lm/W (4000K) |
| Beam Angle                       | 110                       |
| CRI                              | 80                        |
| CCT                              | 3000/4000K                |
| Input                            | 220-240V                  |
| Operating Temp                   | 0°C - 25°C                |
| SDCM                             | 6                         |
| Product Weight without Packaging | 1.234 kg                  |

| TECHNICAL INFORMATION          |               |
|--------------------------------|---------------|
| Light Source                   | LED           |
| Colour / Finish                | White         |
| IP Rating                      | IP20          |
| Class Protection               | 1             |
| Internal / External            | Internal      |
| Surface / Recessed / Suspended | Ceiling, Wall |
| Lumen Depreciation             | L70 60,000h   |
| Warranty (Years)               | 5             |
| CE Mark                        | Yes           |
| Diameter                       | 435 mm        |

