



Category	Bulkheads	
Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Retail	
Specification	Performance	

Eclipse

Eclipse MultiLED CCT Self-Test Emergency White Code: AECLED/W/CCT/M3



PRODUCT FEATURES

- LED wall/ceiling luminaire with adjustable power and light output option suitable for education and commercial applications and ancillary areas
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and $4000\mathrm{K}$
- Spun aluminium base with dished opal Visiluxe diffuser

- One product with integral driver dip-switch
- · Corridor function options available for effective reduction in energy consumption
- BESA box fixing versatile mounting options

	GENERAL INFORMATION
Wattage	10.5/14.5/23W
Lumens Delivered	1200lm - 2800lm (4000K)
Lm/W	108lm/W - 114lm/W (4000K)
Beam Angle	110
CRI	80
ССТ	3000/4000K
Input	220-240V
Operating Temp	5°C - 40°C
SDCM	6
Product Weight without Packag	ging 2.231 kg

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
IK Rating	IK08	
Class Protection]	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 60,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	435 mm	
Emergency Output Duration	3 Hr	

ansell_lightingAnsell Lighting







Category	Bulkheads	
Application	Ancillary, Commercial, Education, Healthcare,	
	Hospitality, Retail	
Specification	Performance	

Eclipse

Eclipse MultiLED CCT Self-Test Emergency White **Code:** AECLED/W/CCT/M3







