



Eclipse

Part of the Bulkheads product category



Model	Eclipse MultiLED CCT White
Code	AECLED/W/CCT
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	8.5W / 21W
Operating Temp	-10°C - 40°C
Lumens Delivered	1020lm - 2520lm (4000K)
lm/W	120 lm/W
CCT	3000/4000K
Beam Angle	110

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	1.887 kg
Colour / Finish	White
Diameter	435 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling, Wall
Power Factor	0.9
L70 @ 25°C	L70 60,000h

PRODUCT FEATURES

- LED wall/ceiling luminaire with adjustable power and light output option suitable for education and commercial applications and ancillary areas
- One product with integral driver dip-switch
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K
- Corridor function options available for effective reduction in energy consumption
- Spun aluminium base with dished opal Visiluxe diffuser





Eclipse



Part of the Bulkheads product category

Model	Eclipse MultiLED CCT White
Code	AECLED/W/CCT
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

