





# Ecoline

Ecoline CCT 1200mm  
Code: AECOLN/CCT/4

<b>Category</b>	Battens and Weatherproofs
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Industrial, Retail
<b>Specification</b>	Performance



## PRODUCT FEATURES

- Slim, robust economic LED batten suitable for ancillary areas and industrial applications
- Supplied complete with versatile mounting clips. Clips can be located anywhere along the spine of the luminaire
- Selectable CCT between 3000K, 4000K and 6500K
- Non-dimmable
- Excellent light uniformity through high transmittance polycarbonate diffuser
- CCT selector conveniently located under batten end cap
- Pre-wired with 600mm cable

GENERAL INFORMATION	
Wattage	30W
Lumens Delivered	3900lm (4000K)
Lm/W	130lm/W (4000K)
Beam Angle	120
CRI	80
CCT	3000/4000/6500K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	6
UGR	25
Product Weight without Packaging	0.39 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Ceiling
Lumen Depreciation	L70 50,000h
Warranty (Years)	3
CE Mark	Yes
Height	27.5 mm

