Eden

Part of the Floodlights product category

Model	Eden 150W Cool White
Code	AEDE/2/150/CW
Application	Outdoor, Residential

GENERAL INFORMATION

Input	220-240V
Wattage	150W
Operating Temp	-20°C to 40°
Lumens Delivered	12150-18150lm
lm/W	100Lm/W±10%
CCT	4000K
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	PC
Product Weight without Packaging	1.318 kg
Colour / Finish	Black
Height	233 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Surface, Wall
Power Factor	0.9
L70 @ 25°C	30000h

PRODUCT FEATURES

- Compact and economic aluminium LED floodlight suitable for semi commercial applications
- Bracket design allows installation without removing mounting bracket
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- Polycarbonate spike accessory allowing installation into lawn and garden applications (10W-30W only)
- Pre-wired with 1 metre of rubber insulated cable for ease of installation





Eden

Part of the Floodlights product category

Model	Eden 150W Cool White
Code	AEDE/2/150/CW
Application	Outdoor, Residential





