



Edge



Part of the Downlights product category

Model	Edge GU10 Fire Rated Gimbal Matt White
Code	AEFRG/MW
Application	Hospitality, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	50W
Operating Temp	0°C - 25°C

MATERIAL INFORMATION

Main Material	Iron
Product Weight without Packaging	0.174 kg
Colour / Finish	Matt White
Diameter	90 mm
Height	105 mm

TECHNICAL INFORMATION



Class Protection	1
Light Source	GU10
Internal / External	Internal
Surface / Recessed / Suspended	Recessed

PRODUCT FEATURES

- Compact Fire Rated downlight for shallow ceiling voids suitable for residential and hospitality applications (product supplied less lamp)
- Protective sheathing spring clips for ceiling protection and ease of installation
- Push fit terminals for fast loop-in, loop-out wiring
- Twistlock lamp retaining ring for ease of lamp replacement
- Ultra-slim bezel profile

ACCESSORIES

AEFRISG	Edge GU10 Fire Rated Gimbal Insulation Support
---------	--





Edge



Part of the Downlights product category

Model Edge GU10 Fire Rated Gimbal Matt White
Code AEFRG/MW
Application Hospitality, Residential, Retail

