



EndLED

Part of the Emergency product category



Model EndLED Lithium Exit Sign Maintained / Non-Maintained White

Code AENLED/LI/3M/ST

Application Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2.5W
Operating Temp	5°C - 40°C
CCT	6000K+/-500K
Beam Angle	75

MATERIAL INFORMATION

Diffuser Material	PMMA
Product Weight without	0.585 kg
Packaging	
Colour / Finish	White
Height	180 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	Ra 80
Internal / External	Internal
Surface / Recessed / Suspended	Wall
Power Factor	0.32
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Low profile compact and modern polycarbonate LED exit box
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Selectable self-test/manual test as standard.
- Supplied with all legend options - arrow down, arrow up and arrow left/right
- 20mm top and rear cable entries





EndLED



Part of the Emergency product category

Model EndLED Lithium Exit Sign Maintained / Non-Maintained White

Code AENLED/LI/3M/ST

Application Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

