



Application	Hospitality, Residential
Specification	Performance

Ergo

Ergo CCT Downlight Black Code: AERGO/1/BK







- Compact polycarbonate LED downlight suitable for residential applications, including kitchens and soffit lighting.
- Adjustable tiltable bezel, offering flexibility for use as a fixed downlight or gimbal
- Low profile design with integral driver with loop-in
- Triac dimmable as standard

- CCT selectable between 3000K, 4000K and 6500K
- IP44 rating as standard allows for a range of installation applications
- Supplied pre-wired with 150mm of cable

GENER	RAL INFORMATION	
Wattage	4W	
Lumens Delivered	480lm (4000K)	
Lm/W	120lm/W	
Beam Angle	40	
CRI	80	
ССТ	3000/4000/6500K	
Input	220/240V	
Operating Temp	-20°C - 45°C	
SDCM	6	
UGR	22	
Cut-Out Size	67-71mm	
Product Weight without Packaging	0.07 kg	

TECHNIC	CAL INFORMATION	
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP44	
IK Rating	IKO2	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 B50 25,000h	
Warranty (Years)	3	
CE Mark	Yes	
Diameter	80 mm	
Height	35 mm	









Application	Hospitality, Residential
Specification	Performance

Ergo

Ergo CCT Downlight Black Code: AERGO/1/BK







