




Application	Hospitality, Residential
Specification	Performance

Ergo

Ergo CCT Downlight White
Code: AERGO/1/WH



- Compact polycarbonate LED downlight suitable for residential applications, including kitchens and soffit lighting.
- Adjustable tiltable bezel, offering flexibility for use as a fixed downlight or gimbal
- Low profile design with integral driver with loop-in
- Triac dimmable as standard
- CCT selectable between 3000K, 4000K and 6500K
- IP44 rating as standard allows for a range of installation applications
- Supplied pre-wired with 150mm of cable

GENERAL INFORMATION	
Wattage	4W
Lumens Delivered	480lm (4000K)
Lm/W	120lm/W
Beam Angle	40
CRI	80
CCT	3000/4000/6500K
Input	220/240V
Operating Temp	-20°C - 45°C
SDCM	6
UGR	22
Cut-Out Size	67-71mm
Product Weight without Packaging	0.07 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP44
IK Rating	IK02
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 B50 25,000h
Warranty (Years)	3
CE Mark	Yes
Diameter	80 mm
Height	35 mm



Application	Hospitality, Residential
Specification	Performance

Ergo

Ergo CCT Downlight White

Code: AERGO/1/WH

