


Ergo Gimbal

Ergo Eco Gimbal Cool White Code: AERGO/GIM/CW






Category

Application

Specification



Ancillary, Hospitality, Residential, Retail

- Compact polycarbonate LED downlight and gimbal suitable for residential applications and semi-commercial applications (gimbal version only)
- Low profile design with integral driver with loop-in, loop-out terminals for ease and speed of Supplied pre-wired with 200mm of cable installation
- Triac dimmable as standard

•	$\ensuremath{IP44}$ rating as standard allows for a range of installation applications (downlight version
	only)

Downlights

Performance

GENERAL INFORMATION			
Wattage	5W		
Lumens Delivered	560lm		
Lm/W	112Im/W		
Beam Angle	40		
CRI	80		
ССТ	4000K		
Input	220-240V		
Operating Temp	-20°C - 40°C		
SDCM	6		
UGR	26		
Cut-Out Size	68mm		
Product Weight without Packaging	0.09 kg		

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Matt White		
IP Rating	IP20		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Recessed		
Lumen Depreciation	L70 25,000h		
Warranty (Years)	2		
CE Mark	Yes		
Height	37 mm		

