



@ansell\_lighting



ansellighting



Ansell Lighting





ansell\_lighting

# Endurance 1200x600

Endurance TP(a) 1200x600 Panel DSI Daylight

Code: AERMLED2/120/DL/DD2

Category	Commercial Panels
Application	Ancillary, Commercial, Education, Healthcare, Retail
Specification	Performance



- Edge lit LED panel suitable for education, commercial and ancillary area applications
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option
- TP(a) as standard

- Cool white, warm white and daylight options
- Low glare and even light distribution for multiple applications
- Powered by Tridonic

GENERAL INFORMATION	
Wattage	60W
Lumens Delivered	5300lm
Lm/W	87lm/W
Beam Angle	110
CRI	80
CCT	6000K
Input	220-240V
Operating Temp	-20°C - 40°C
SDCM	3
UGR	20
Cut-Out Size	585x1185mm
Product Weight without Packaging	0.01 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface, Suspended
Lumen Depreciation	L80 76,000h
Warranty (Years)	5
CE Mark	Yes
Accessories	AERMLED/120/SMF, APRK/120

