





Endurance 1200x300

Endurance TP(a) 1200x300 Panel OCTO Smart
Code: AERMLED2/30/CW/OCTO

| | |
|---------------|--|
| Category | Commercial Panels |
| Application | Ancillary, Commercial, Education, Healthcare, Retail |
| Specification | Performance |



PRODUCT FEATURES

- Edge lit LED panel suitable for education, commercial and ancillary area applications
- White anodised aluminium frame for visual compatibility with ceiling grid
- Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC
- Cool white, warm white and daylight options
- Surface mounting frame option
- Self-Test Panel Pod and Sensor Pod compatible

| GENERAL INFORMATION | |
|----------------------------------|--------------|
| Wattage | 30W |
| Lumens Delivered | 3300lm |
| Lm/W | 105lm/W |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 4000K |
| Input | 220-240V |
| Operating Temp | -20°C - 40°C |
| SDCM | 4 |
| UGR | 21 |
| Cut-Out Size | 285x1185mm |
| Product Weight without Packaging | 2.157 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------------------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP40 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed, Surface, Suspended |
| Lumen Depreciation | L80 76,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Accessories | AERMLED/SK, AERMLED/30/SMF, APRK/30 |

