Endurance

Part of the Commercial Panels product category

Model	Endurance TP(a) 1200x300 Panel Cool White
Code	AERMLED2/30/CW
Application	Ancillary, Commercial, Education, Healthcare, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	31W
Operating Temp	-20°C to 40°C
Lumens Delivered	3300lm
lm/W	105lm/W
CCT	4000K
UGR	21
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	PP
Product Weight without Packaging	2.38 kg
Colour / Finish	White
Height	10 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 100,000h

PRODUCT FEATURES

- Edge lit LED panel suitable for education, commercial and ancillary area applications
- Cool white, warm white and daylight options
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option
- Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC

ACCESSORIES

APOD/1/3NM/DA	Panel Pod PRO DALI
ASMF30/1	Surface Mounting Frame 1200x300
APRK/30	1200x300 Plasterboard Recessed Kit
ADDIM/30/MC	Multi-current Dimmable Driver 30W
AIRMLED/POD/3NM/ST	Panel Pod Self-Test Emergency
AIRMLED/POD/MWS	Panel Pod Sensor





Endurance

Part of the Commercial Panels product category

Model	Endurance TP(a) 1200x300 Panel Cool White
Code	AERMLED2/30/CW
Application	Ancillary, Commercial, Education, Healthcare, Retail













