



Category	Commercial Panels	
Application	Ancillary, Commercial, Education, Healthcare, Retail	
Specification	Performance	

Endurance 1200x300

Endurance TP(a) 1200x300 Panel Cool White Code: AERMLED2/30/CW

PRODUCT FEATURES

- Edge lit LED panel suitable for education, commercial and ancillary area applications
- · White anodised aluminium frame for visual compatibility with ceiling grid
- Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC
- Cool white, warm white and daylight options
- Surface mounting frame option
- Self-Test Panel Pod and Sensor Pod compatible

GENERAL INFORMATION		
Wattage	31W	
Lumens Delivered	3300lm	
Lm/W	105lm/W	
Beam Angle	110	
CRI	80	
CCT	4000K	
Input	220/240V	
Operating Temp	-20? to 40?	
SDCM	6	
UGR	21	
Product Weight without Packaging	2.38 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP40	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Recessed, Suspended	
Lumen Depreciation	L80 76,000h	
Warranty (Years)	5	
CE Mark	Yes	
Accessories	AERMLED/SK, AERMLED/30/SMF, APRK/30	













Category	Commercial Panels	
Application	Ancillary, Commercial, Education, Healthcare, Retail	
Specification	Performance	

Endurance 1200x300

Endurance TP(a) 1200x300 Panel Cool White Code: AERMLED2/30/CW





ACCESSORIES		
APOD/1/3NM/DA	Panel Pod PRO DALI Emergency	
ASMF30/1	Surface Mounting Frame 1200x300	
APRK/30	1200x300 Plasterboard Recessed Kit	
ADDIM/30/MC	Multi-current Dimmable Driver 30W	
AIRMLED/POD/3NM/ST	Panel Pod Self-Test Emergency	
AIRMLED/POD/MWS	Panel Pod Sensor	





