



Endurance 1200x300

Endurance TP(a) 1200x300 Panel 1-10V Daylight Code: AERMLED2/30/DL/DD4

Category	Commercial Panels
Application	Ancillary, Commercial, Education, Healthcare, Retail
Specification	Performance



- Edge lit LED panel suitable for education, commercial and ancillary area applications
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option
- TPa as standard

- Cool white, warm white and daylight options
- Low glare and even light distribution for multiple applications

295

• Powered by Tridonic

GENERAL INFORMATION		
Wattage	30W	
Lumens Delivered	3300lm	
Lm/W	103lm/W	
Beam Angle	110	
CRI	80	
ССТ	6500K	
Input	220/240V	
Operating Temp	-20°C - 40°C	
SDCM	4	
UGR	21	
Cut-Out Size	285x1185mm	

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	White		
IP Rating	IP40		
Class Protection	2		
Internal / External	Internal		
Surface / Recessed / Suspended	Ceiling, Recessed, Suspended		
Lumen Depreciation	L80 76,000h		
Warranty (Years)	5		
CE Mark	Yes		
Accessories	Aermled/SK, Aermled/30/SMF, Aprk/30		

