




Endurance 1200x300

Endurance TP(a) 1200x300 Panel 1-10V Warm Code: AERMLED2/30/WW/DD4

| Category | Commercial Panels |
|---------------|--|
| Application | Ancillary, Commercial, Education, Healthcare, Retail |
| Specification | Performance |





PRODUCT FEATURES

- Edge lit LED panel suitable for education, commercial and ancillary area applications
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option
- TPa as standard

- Cool white, warm white and daylight options
- Low glare and even light distribution for multiple applications
- Powered by Tridonic

| GENERAL INFORMATION | | |
|---------------------|--------------|--|
| Wattage | 30W | |
| Lumens Delivered | 3200lm | |
| Lm/W | 103lm/W | |
| Beam Angle | 110 | |
| CRI | 80 | |
| CCT | 3000K | |
| Input | 220/240V | |
| Operating Temp | -20°C - 40°C | |
| SDCM | 4 | |
| UGR | 21 | |
| Cut-Out Size | 285x1185mm | |

| TECHNICAL INFORMATION | | | |
|--------------------------------|-------------------------------------|--|--|
| Light Source | LED | | |
| Colour / Finish | White | | |
| IP Rating | IP40 | | |
| Class Protection | 2 | | |
| Internal / External | Internal | | |
| Surface / Recessed / Suspended | Ceiling, Recessed, Suspended | | |
| Lumen Depreciation | L80 76,000h | | |
| Warranty (Years) | 5 | | |
| CE Mark | Yes | | |
| Accessories | AERMLED/SK, AERMLED/30/SMF, APRK/30 | | |