Endurance

Part of the Commercial Panels product category

Model	Endurance TP(a) 600x600 Panel Cool White
Code	AERMLED2/60/CW
Application	Ancillary, Commercial, Education, Healthcare, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	30W
Operating Temp	-20°C - 40°C
Lumens Delivered	3100lm
lm/W	103lm/W
CCT	4000K
UGR	21
Beam Angle	110

MATERIAL INFORMATION

Diffuser Material	PP
Product Weight without Packaging	2.077 kg
Colour / Finish	White

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface, Suspended
Power Factor	0.9
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Edge lit LED panel suitable for education, commercial and ancillary area applications
- Cool white, warm white and daylight options
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option
- TPa as standard

ACCESSORIES

APOD/1/3NM/DA	Panel Pod PRO DALI
AERMLED/SK	Endurance Panel Suspension Kit
ASMF60/1	Surface Mounting Frame 600x600
AERMLED/60/CGCB/KIT	Endurance 600x600 Concealed Grid Ceiling Kit
APRK/60	600x600 Plasterboard Recessed Kit
AARX60K/1	ARX 600x600 Anti-Ligature Kit
ASRF/60/1	600x600 Skylight Recessed Frame
ADDIM/30/MC	Multi-current Dimmable Driver 30W





Endurance

Part of the Commercial Panels product category

Model	Endurance TP(a) 600x600 Panel Cool White
Code	AERMLED2/60/CW
Application	Ancillary, Commercial, Education, Healthcare, Retail











