



Endurance



Part of the Commercial Panels product category

Model	Endurance TP(a) UGR<19 1200x600 Panel Daylight
Code	AERMLED3/120/DL
Application	Ancillary, Commercial, Education, Healthcare, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	60W
Operating Temp	-20? to 40?
Lumens Delivered	5400lm
lm/W	90lm/W
CCT	6000K
UGR	17
Beam Angle	80

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	PS
Product Weight without Packaging	4.843 kg
Colour / Finish	White
Height	10 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface
Power Factor	0.9
L70 @ 25°C	L70 B50 100,000h

PRODUCT FEATURES

- Edge lit LED panel suitable for education, commercial and ancillary area applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Cool white, warm white and daylight options
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option

ACCESSORIES

APOD/1/3NM/DA	Panel Pod PRO DALI
ASMF120/1	Surface Mounting Frame 1200x600
APRK/120	1200x600 Plasterboard Recessed Kit
ADDIM/60/MC	Multi-current Dimmable Driver 60W
AIRMLED/POD/3NM/ST	Panel Pod Self-Test Emergency
AIRMLED/POD/MWS	Panel Pod Sensor





Endurance



Part of the Commercial Panels product category

- Model** Endurance TP(a) UGR<19 1200x600 Panel Daylight
- Code** AERMLED3/120/DL
- Application** Ancillary, Commercial, Education, Healthcare, Retail

