












Endurance UGR<19 1200x600

Endurance TP(a) UGR<19 1200x600 Panel 1-10V


Code: AERMLED3/120/WW/DD4











- Edge lit LED panel suitable for education, commercial and ancillary area applications
- · Cool white, warm white and daylight options
- $\bullet\,$ Low glare and even light distribution for multiple applications
- Powered by Tridonic

- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- White anodised aluminium frame for visual compatibility with ceiling grid
- Surface mounting frame option
- TPa as standard

GENERAL INFORMATION		
Wattage	60W	
Lumens Delivered	5400lm	
Lm/W	90lm/W	
Beam Angle	80	
CRI	80	
CCT	3000K	
Input	220-240V	
Operating Temp	-20°C - 40°C	
SDCM	3	
UGR	17	
Cut-Out Size	585x1185mm	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP44	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed, Surface	
Lumen Depreciation	L80 76,000h	
Warranty (Years)	5	
CE Mark	Yes	
Accessories	AERMLED/120/SMF, APRK/120	

www.ansell-lighting.com Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

