



Falcon



Part of the Emergency product category

Model Falcon Surface Emergency Downlight IP65 Non-Maintained White
Code AFALED/3NM/ST/IP65
Application Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2.6W
Operating Temp	0°C - 40°C
Lumens Delivered	Open area - 153lm Escape route - 145lm
lm/W	59lm/W
CCT	6500K
Beam Angle	Open area - 96 / Escape route - 135x15

MATERIAL INFORMATION

Main Material	Polycarbonate
Product Weight without	0.559 kg
Packaging	
Colour / Finish	White
Height	57.2 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	6
CRI	70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling
Power Factor	0.27
L70 @ 25°C	L70 B50 50,000h

PRODUCT FEATURES

- Compact surface ultra-low profile recessed self-test emergency downlight
- Supplied with open area and escape route interchangeable lenses
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Up to 19.6 metres spacing between luminaires





Falcon



Part of the Emergency product category

- Model** Falcon Surface Emergency Downlight IP65 Non-Maintained White
- Code** AFALED/3NM/ST/IP65
- Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

