



ForceLINE

Part of the High/Low Bay product category



Model ForceLINE Linear 600mm
Code AFLLED2
Application Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	150W
Operating Temp	-20°C - 25°C
Lumens Delivered	16500lm
lm/W	110lm/W
CCT	4000K
Beam Angle	105

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	4.74 kg
Colour / Finish	Graphite
Height	113 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	5
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Suspended
Power Factor	0.98
L70 @ 25°C	L70 B50 51,000h

PRODUCT FEATURES

- Powerful and robust IP65 low/high bay suitable for industrial applications
- Mounting brackets supplied as standard for dropprod or chain/wire installation (suspension kit not included)
- Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan
- Anti-glare polycarbonate diffuser maximises performance and light output
- Powered by Philips





ForceLINE



Part of the High/Low Bay product category

Model ForceLINE Linear 600mm
Code AFLLED2
Application Industrial

