



# Falcon



Part of the Emergency product category

<b>Model</b>	Falcon Pro DALI Surface Mounted Downlight Black
<b>Code</b>	AFLP/1/B/3NM/DA
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	2W
<b>Operating Temp</b>	5°C - 50°C
<b>Lumens Delivered</b>	223lm(OA) 228lm(ER)
<b>lm/W</b>	111lm/W
<b>CCT</b>	6500K+/-500K
<b>Beam Angle</b>	Open area - 125° / Escape route - 75°/135°

## MATERIAL INFORMATION

<b>Main Material</b>	Polycarbonate
<b>Diffuser Material</b>	Polycarbonate
<b>Product Weight without Packaging</b>	0.37 kg
<b>Colour / Finish</b>	Black
<b>Height</b>	49 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	2
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	6
<b>CRI</b>	Ra 70
<b>Internal / External</b>	Internal / External
<b>Surface / Recessed / Suspended</b>	Ceiling
<b>Power Factor</b>	0.3
<b>L70 @ 25°C</b>	L70 B50 73,000h

## PRODUCT FEATURES

- Compact surface ultra-low profile recessed DALI emergency downlight
- Supplied with open area and escape route interchangeable lenses
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Selectable self-test/manual test as standard.





# Falcon



Part of the Emergency product category

- Model** Falcon Pro DALI Surface Mounted Downlight Black
- Code** AFLP/1/B/3NM/DA
- Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

