



Falcon



Part of the Emergency product category

Model	Falcon Pro DALI Surface Mounted Downlight White
Code	AFLP/1/W/3NM/DA
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2W
Operating Temp	5°C - 50°C
Lumens Delivered	223lm(OA) 228lm(ER)
lm/W	111lm/W
CCT	6500K+/-500K
Beam Angle	Open area - 125° / Escape route - 75°/135°

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.37 kg
Colour / Finish	White
Height	49 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	Ra 70
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling
Power Factor	0.3
L70 @ 25°C	L70 B50 73,000h

PRODUCT FEATURES

- Compact surface ultra-low profile recessed DALI emergency downlight
- Supplied with open area and escape route interchangeable lenses
- High specification optic design and performance allows increased spacing providing reduced cost
- Available in black and white finishes
- Selectable self-test/manual test as standard.





Falcon



Part of the Emergency product category

- Model** Falcon Pro DALI Surface Mounted Downlight White
- Code** AFLP/1/W/3NM/DA
- Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

