






Galaxy

Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Code: AGALED/DD3/SM3



- Multi-wattage compact IP65 LED performance downlight suitable for education, commercial and healthcare applications
- Fitting and driver pre-wired with ST18 connectors
- Removable twist on, twist off bezel provides option of utilising alternative bezel and drop glass accessories
- Powered by Philips
- Cut-out dimensions suitable to replace most PLC downlights
- Faceted reflector and optical fresnel lens provides outstanding performance, uniformity and glare control
- Dimmable and Emergency options

GENERAL INFORMATION

Wattage	11W - 16W
Lumens Delivered	1400lm - 2000lm (4000K)
Lm/W	131lm/W - 125lm/W (4000K)
Beam Angle	100
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	0°C - 35°C
SDCM	5
UGR	24
Cut-Out Size	210mm

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 100,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	226 mm
Height	70 mm

