



@ansell\_lighting



ansellighting



Ansell Lighting







ansell\_lighting

# Galaxy

Galaxy CCT MultiLED Downlight OCTO Smart  
Code: AGALED/OCTO/M3

|               |   |
|---------------|---|
| Category      | Downlights  |
| Application   | Ancillary, Commercial, Education, Healthcare, Hospitality, Retail |
| Specification | Performance   |



## PRODUCT FEATURES

- Multi-wattage compact IP65 LED performance downlight suitable for education, commercial and healthcare applications
- Fitting and driver pre-wired with ST18 connectors
- Removable twist on, twist off bezel provides option of utilising alternative bezel and drop glass accessories
- Powered by Philips
- Cut-out dimensions suitable to replace most PLC downlights
- Faceted reflector and optical fresnel lens provides outstanding performance, uniformity and glare control
- Dimmable and Emergency options

## GENERAL INFORMATION

|                                  |                           |
|----------------------------------|---------------------------|
| Wattage                          | 16W                       |
| Lumens Delivered                 | 1400lm - 2000lm (4000K)   |
| Lm/W                             | 131lm/W - 125lm/W (4000K) |
| Beam Angle                       | 100                       |
| CRI                              | 80                        |
| CCT                              | 3000/4000K                |
| Input                            | 220-240V                  |
| Operating Temp                   | 0°C - 35°C                |
| SDCM                             | 5                         |
| UGR                              | 24                        |
| Cut-Out Size                     | 210mm                     |
| Product Weight without Packaging | 2.812 kg                  |

## TECHNICAL INFORMATION

|                                |              |
|--------------------------------|--------------|
| Light Source                   | LED          |
| Colour / Finish                | White        |
| IP Rating                      | IP65         |
| Class Protection               | 2            |
| Internal / External            | Internal     |
| Surface / Recessed / Suspended | Recessed     |
| Lumen Depreciation             | L70 100,000h |
| Warranty (Years)               | 5            |
| CE Mark                        | Yes          |
| Diameter                       | 226 mm       |
| Height                         | 70 mm        |

