





Downlights

Hospitality, Retail

Performance

@ansell\_lighting






in Ansell Lighting



## Galaxy

## Galaxy CCT MultiLED Downlight Self-Test Code: AGALED/SM3







Category

**Application** 

Specification



Ancillary, Commercial, Education, Healthcare,

## PRODUCT FEATURES

- Multi-wattage compact IP65 LED performance downlight suitable for education, commercial
  Cut-out dimensions suitable to replace most PLC downlights and healthcare applications
- Fitting and driver pre-wired with ST18 connectors
- Removable twist on, twist off bezel provides option of utilising alternative bezel and drop glass accessories
- · Powered by Philips

- Faceted reflector and optical fresnel lens provides outstanding performance, uniformity and glare control
- Dimmable and Emergency options

GENERAL INFORMATION		
Wattage	11W - 16W	
Lumens Delivered	1400lm - 2000lm (4000K)	
Lm/W	131lm/W - 125lm/W (4000K)	
Beam Angle	100	
CRI	80	
ССТ	3000/4000K	
Input	220-240V	
Operating Temp	0°C - 35°C	
SDCM	5	
UGR	24	
Cut-Out Size	210mm	
Product Weight without Packagi	ing 1.45 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP65	
Class Protection	2	
Internal / External	Internal	
Surface / Recessed / Suspended	Recessed	
Lumen Depreciation	L70 100,000h	
Warranty (Years)	5	
CE Mark	Yes	
Diameter	226 mm	
Height	70 mm	
Accessories	AGPL/DG1/W, AGPL/DG3/W	