













## Gamma

Gamma CCT Emergency Code: AGAMLED/CCT/M3



Category	Bulkheads
Application	Ancillary, Commercial, Hospitality, Residential, Retail
Specification	Performance





- Ultra slim modern polycarbonate wall/ceiling light suitable for education, residential and ancillary applications
- CCT selectable between 3000K and 4000K
- Microwave sensor set to 15 minutes at 3 metres (non-adjustable)
- /MWS and MWS/M3 has integral photocell isolation switch

- Matt white finish to body and diffuser with optional chrome trim ring
- Rear fixing bracket and terminal housing for ease of installation
- /MWS and /MWS/M3 versions operate as Primary and can be used in conjunction with standard Secondary
- Non-dimmable

GENER	AL INFORMATION	
Wattage	17W	
Lumens Delivered	1800lm (4000K)	
Lm/W	106lm/W (4000K)	
Beam Angle	110	
CRI	80	
CCT	3000/4000K	
Input	220-240V	
Operating Temp	5°C - 35°C	
SDCM	6	
Product Weight without Packaging	1.368 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Matt White	
IP Rating	IP54	
Class Protection	2	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Wall	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	3	
CE Mark	Yes	
Diameter	296 mm	
Accessories	AGAMLEDBZ/CH	

**www.ansell-lighting.com** Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

