



Category	Bulkheads
Application	Ancillary, Commercial, Hospitality, Residential, Retail
Specification	Performance

## Gamma

Gamma CCT







## PRODUCT FEATURES

- Ultra slim modern polycarbonate wall/ceiling light suitable for education and residential applications and ancillary areas
- CCT selectable between 3000K and 4000K
- Microwave sensor set to 15 minutes at 3 metres (non-adjustable)
- /MWS and MWS/M3 has integral photocell isolation switch

- Matt white finish to body and diffuser with optional chrome trim ring
- Rear fixing bracket and terminal housing for ease of installation  $% \left( 1\right) =\left( 1\right) \left( 1\right)$
- /MWS and /MWS/M3 versions operate as Primary and can be used in conjunction with standard Secondary
- Non-dimmable

	GENERAL INFORMATION
Wattage	17W
Lumens Delivered	1800lm (4000K)
Lm/W	106lm/W (4000K)
Beam Angle	110
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	-5°C - 35°C
SDCM	6
Product Weight without Packagi	<b>ng</b> 1.053 kg

CAL INFORMATION	
LED	
Matt White	
IP54	
2	
Internal / External	
Ceiling, Wall	
L70 54,000h	
3	
Yes	
296 mm	
AGAMLEDBZ/CH	
	LED Matt White IP54 2 Internal / External Ceiling, Wall L70 54,000h 3 Yes 296 mm













Category	Bulkheads
Application	Ancillary, Commercial, Hospitality, Residential, Retail
Specification	Performance

## Gamma

Gamma CCT

Code: AGAMLED/CCT





	ACCESSORIES
AGAMLEDBZ/CH	Gamma Chrome Trim Ring





