






Unity GC Pro

| | |
|---------------|---|
| Application | Ancillary, Commercial, Hospitality, Residential, Retail |
| Specification | Architectural |

Unity GC Pro 1 Fixed Downlight Warm White
Code: AGCP1/1/WW



PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated
- Remote driver with plug and play connection
- Deep cut-off angle for glare control and comfort
- Mirror finished anodized reflector for optimum light control

| GENERAL INFORMATION | |
|----------------------------------|----------|
| Wattage | 3W |
| Lumens Delivered | 130lm |
| Lm/W | 43lm/W |
| Beam Angle | 30 |
| CRI | 95 |
| CCT | 3000K |
| Input | 220-240V |
| Operating Temp | -20~25 |
| SDCM | 3 |
| UGR | 10 |
| Cut-Out Size | 40 |
| Energy efficiency class | F |
| Product Weight without Packaging | 0.075 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 50 mm |
| Height | 53 mm |

