




Unity GC Pro

| | |
|----------------------|---|
| Application | Ancillary, Commercial, Hospitality, Residential, Retail |
| Specification | Architectural |

Unity GC Pro 2 Fixed Downlight Warm White DALI
Code: AGCP2/1/WW/DD3



PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated
- Remote driver with plug and play connection
- Deep cut-off angle for glare control and comfort
- Mirror finished anodized reflector for optimum light control

| GENERAL INFORMATION | |
|----------------------------------|-----------------------------------|
| Wattage | 7W |
| Lumens Delivered | 280lm |
| Lm/W | 40lm/W |
| Beam Angle | 30 |
| CRI | 95 |
| CCT | 3000K |
| Input | 220/240V |
| Operating Temp | -20 ° -25 ° |
| SDCM | 3 |
| UGR | 10 |
| Cut-Out Size | 50 |
| Product Weight without Packaging | 0.153 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP44 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L80 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |

