













Unity GC Pro

 Application
 Ancillary, Commercial, Hospitality, Residential, Retail

 Specification
 Architectural

Unity GC Pro 3 Fixed Downlight Cool White DALI Code: AGCP3/1/CW/DD3







PRODUCT FEATURES

- Compact high performance architectural adjustable downlight suitable for residential applications
- Die-cast aluminium construction, powder coated
- Remote driver with plug and play connection

www.ansell-lighting.com

- Deep cut-off angle for glare control and comfort
- Mirror finished anodized reflector for optimum light control

GENERAL INFORMATION		
Wattage	14W	
Lumens Delivered	780lm	
Lm/W	57lm/W	
Beam Angle	30	
CRI	95	
ССТ	4000K	
Input	220-240V	
Operating Temp	-20⊠-25⊠	
SDCM	3	
UGR	10	
Cut-Out Size	68	
Product Weight without Packagin	ng 1.067 kg	

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L80 54,000h
Warranty (Years)	5
CE Mark	Yes

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750