











Commercial Linear

Ancillary, Retail

Performance




## Gemini

## Gemini CCT Surface/Suspended Linear 1200mm Code: AGELED4/DD4/DM3








Category **Application** 

Specification



- $\bullet \ \ \text{High specification fully enclosed linear luminaire suitable for most commercial and}$ educational applications
- Microprism diffuser for enhanced photometric performance
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2  $\,$ outputs, in one luminaire
- · Powered by Philips

- Push pin release design feature ensures a quick and easy installation
- · Robust steel construction
- Suitable for surface and suspension

GENERAL INFORMATION	
Wattage	35W
Lumens Delivered	2900lm - 4700lm (4000K)
Lm/W	135lm/W (4000K)
Beam Angle	70
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	0°C - 50°C
SDCM	3
UGR	18

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	White	
IP Rating	IP20	
Class Protection	1	
Internal / External	Internal	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	55 mm	